



HI 900 **Indirect Fired Air Heaters**

HI 900 Skid Mounted Indirect Fired Air Heater

The most versatile, robust indirect fired air heaters producing clean, moisture free air for various heating and drying applications. The HI 900 is easy to set-up and simple to operation making these units extremely user friendly, and can operate on diesel, natural gas or propane for maximum job site convenience. All models are CSA certified.

- Indirect fired air heaters produce clean, dry, healthy heat offering an ideal environment for a variety of construction, residential and restoration applications without the use of an open flame, combustion carbons or water.
- The unique Recircul-Air design allows adjustable recirculation of warm inside air, while pressurizing with fresh air, resulting in fuel savings and even temperatures.
- Industry leading for heat delivery in its class, boasting up to 878,000 Btu/hr and up to 6,450 cubic feet per minute, the HI 900 also features a static pressure gauge, helping maximize heat delivery and avoid output air restrictions.
- Optional "plug and play" burners can easily be swapped between diesel and NG/LP and units feature extra-large burner compartment for ideal service access or simple burner conversion.
- Designed for maximum mobility with integrated forklift pockets and a single lift point, the HI 900 is able to fit through a 36" door opening.

**HI 900****Indirect Fired Air Heaters**

Technical specifications

HI 900

	HI 900D	HI 900G
Dimensions		
L x W x H Overall in	139 x 47 x 77	139 x 47 x 77
L x W x H Shipping in	151 x 50 x 84	151 x 50 x 84
Weight without Fuel lb	2,567	2,874
Operating weight with Fuel lb	3,400	2,550
Operating data		
Diameter Air Outlets (qty 2) in	20	20
Diameter Air Outlets (qty 2) in	16	16
Diameter Air Outlets (qty 4) in	12	12
Diameter Air Inlet (qty 2) in	20	20
Heating power Heat Input BTU/h	878,000	850,000
Heat efficiency %	83	83
Operating temperature Air Temperature Rise ° F	108	108
Capacity Sizing Air Heat ft ³	1,214,500	1,214,500
Capacity Drying Size ft ³	432,230	432,230
Fuel type	Diesel	NG / LP
Fuel consumption Burner Diesel US gal/h	6.1	0
Fuel consumption (liquid propane) Burner (NG) ft ³ /h	0	850
Fuel consumption Burner (LP) US gal/h	0	8.19
Operating performance Burner hp	0.33	0.33
at rpm Burner rpm	3,450	3,450
Tank capacity Burner US gal	103	0
Runtime Burner (100%) h	16.9	0
Runtime Burner (75%) h	22.5	0
Engine / Motor type Blower	Centrifugal	Centrifugal
Power Blower hp	5	5
RPM / speed Blower rpm	3,450	3,450
Air flow CFM	6,447	6,447
Static Pressure W.C. (inch)	2	2



	HI 900D	HI 900G
Length Max Duct - 2 x 20in Supply ft	200	200
Length Max Duct - 2 x 16in Supply ft	100	100
Length Max Duct - 4 x 12in Supply ft	100	100
Length Max Duct - 2 x 20in Return ft	50	50
Electrical system		
Engine / Motor		

Information on suitable accessories can be found on our website.

The right to make changes is reserved in the interests of ongoing further developments. You can find more information on the engine power in the operator's manual. The actual power output figures may vary due to specific operating conditions.

Information on suitable accessories can be found on our website. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2014 Wacker Neuson SE.